

FB312-91

PAGE 1

SECTION 1

PRODUCT IDENTIFIER FB312-91 HEAVY DUTY GLOSS ENAMEL, BASE 1
DATE OF PREPARATION JANUARY 5, 2010
PRODUCT USE PROTECTIVE COATING

MANUFACTURED BY: AKZO NOBEL PAINTS LLC, 15885 WEST SPRAGUE ROAD,
STRONGSVILLE, OHIO 44136, U.S.A
ICI PAINTS (CANADA), 8200 KEELE STREET,
CONCORD, ONTARIO L4K 2A5, CANADA.

EMERGENCY AND MSDS TELEPHONE NUMBER:
1-800-545-2643

MSDS PREPARED BY: PRODUCT SAFETY AND COMPLIANCE DEPARTMENT
AKZO NOBEL PAINTS LLC

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT

WT. %:

CHEMICAL NAME LONG OIL ALKYD RESIN
COMMON NAME : LONG OIL ALKYD RESIN
CAS NUMBER: CONFIDENTIAL

20-30

CHEMICAL NAME LONG OIL ALKYD RESIN
COMMON NAME : LONG OIL ALKYD RESIN
CAS NUMBER: CONFIDENTIAL

10-20

CHEMICAL NAME BENZENE, ETHYL-
COMMON NAME : ETHYLBENZENE
CAS NUMBER: 100-61-4

.1-1.0

CHEMICAL NAME QUATERNARY AMMONIUM COMPOUNDS, BENZYLBI-
(HYDROGENATED TALLOW ALKYL)METHYL, BENZOATE LAURYL
COMMON NAME : RHEOLOGICAL ADDITIVE
CAS NUMBER: 121888-66-2

1-5

CHEMICAL NAME BENZENE, DIMETHYL-
COMMON NAME : XYLENE

1-5

FB312-91

PAGE 2

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

CAS NUMBER:	1330-20-7	
CHEMICAL NAME	KAOLIN	
COMMON NAME :	CLAY	1-5
CAS NUMBER:	1330-58-7	
CHEMICAL NAME	TITANIUM OXIDE	
COMMON NAME :	TITANIUM DIOXIDE	10-20
CAS NUMBER:	13443-67-7	
CHEMICAL NAME	HEXANOIC ACID, 2-ETHYL-, ZIRCONIUM SALT	
COMMON NAME :	ZIRCONIUM CARBOXYLATE	1-5
CAS NUMBER:	22464-99-9	
CHEMICAL NAME	BENZENESULFONIC ACID, DODECYL-, COMPOUND WITH	
	2-PROPANAMINE (1:1)	1-5
COMMON NAME :	ISOEROPYLAMINE DODECYLBENZENESULFONATE	
CAS NUMBER:	26264-05-1	
CHEMICAL NAME	NAPHTHA (PETROLEUM), HEAVY ALKYLATE	
COMMON NAME :	HEAVY SOLVENT NAPHTHA	5-10
CAS NUMBER:	64741-65-7	
CHEMICAL NAME	SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPHATIC	
COMMON NAME :	MEDIUM ALIPHATIC SOLVENT NAPHTHA	10-20
CAS NUMBER:	64742-88-7	
CHEMICAL NAME	STODDARD SOLVENT	
COMMON NAME :	MINERAL SPIRITS	1-5
CAS NUMBER:	8052-41-3	
CHEMICAL NAME	BENZENE, 1,2,4-TRIMETHYL-	
COMMON NAME :	PSEUDOCUMENE	.1-1.0
CAS NUMBER:	95-63-6	

FB312-91

PAGE 3

SECTION 3: HAZARDS IDENTIFICATION

PRIMARY ROUTE(S) OF EXPOSURE

INHALATION, SKIN CONTACT, EYE CONTACT, INGESTION.

EFFECTS OF OVEREXPOSURE**INHALATION**

IRRITATION OF RESPIRATORY TRACT. PROLONGED INHALATION MAY LEAD TO LOSS OF APPETITE, MUCOUS MEMBRANE IRRITATION, FATIGUE, DROWSINESS, DIZZINESS AND/OR LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, VOMITING, BLURRED VISION, COUGHING, DIFFICULTY WITH SPEECH, CENTRAL NERVOUS SYSTEM DEPRESSION, INTOXICATION, ANESTHETIC EFFECT OR NARCOSIS, DIFFICULTY OF BREATHING, TREMORS, SEVERE LUNG IRRITATION OR DAMAGE, LIVER DAMAGE, KIDNEY DAMAGE, PULMONARY EDEMA, CONVULSIONS, PNEUMOCONIOSIS, LOSS OF CONSCIOUSNESS, RESPIRATORY FAILURE, ASPHYXIATION, DEATH.

SKIN CONTACT

IRRITATION OF SKIN. PROLONGED OR REPEATED CONTACT CAN CAUSE DERMATITIS, DEFATTING, BLISTERING. SKIN CONTACT MAY RESULT IN DERMAL ABSORPTION OF COMPONENT(S) OF THIS PRODUCT WHICH MAY CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION.

EYE CONTACT

IRRITATION OF EYES. PROLONGED OR REPEATED CONTACT CAN CAUSE CONJUNCTIVITIS, BLURRED VISION, TEARING OF EYES, REDNESS OF EYES, SEVERE EYE IRRITATION.

INGESTION

INGESTION MAY CAUSE LUNG INFLAMMATION AND DAMAGE DUE TO ASPIRATION OF MATERIAL INTO LUNGS, MOUTH AND THROAT IRRITATION, MUCOUS MEMBRANE IRRITATION, FATIGUE, DIZZINESS AND/OR LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, VOMITING, DIARRHEA, GASTRO-INTESTINAL DISTURBANCES, CENTRAL NERVOUS SYSTEM DEPRESSION, DIFFICULTY OF BREATHING, LIVER DAMAGE, KIDNEY DAMAGE, PULMONARY EDEMA, CONVULSIONS, LOSS OF CONSCIOUSNESS.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

EYE, SKIN, RESPIRATORY DISORDERS, LUNG DISORDERS, KIDNEY DISORDERS, LIVER DISORDERS.

FB312-91

PAGE 4

SECTION 4: FIRST-AID MEASURES

INHALATION REMOVE TO FRESH AIR. RESTORE AND SUPPORT CONTINUED BREATHING.
GET EMERGENCY MEDICAL ATTENTION.
HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY. GET MEDICAL HELP FOR ANY BREATHING DIFFICULTY.
REMOVE TO FRESH AIR IF INHALATION CAUSES EYE WATERING, HEADACHES, DIZZINESS, OR OTHER DISCOMFORT.

SKIN CONTACT WASH THOROUGHLY WITH SOAP AND WATER. IF ANY PRODUCT REMAINS, GENTLY RUB PETROLEUM JELLY, VEGETABLE OR MINERAL/BABY OIL ONTO SKIN. REPEATED APPLICATIONS MAY BE NEEDED. REMOVE CONTAMINATED CLOTHING.
WASH CONTAMINATED CLOTHING BEFORE RE-USE.

EYE CONTACT FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER, ESPECIALLY UNDER LIDS FOR AT LEAST 15 MINUTES. IF IRRITATION OR OTHER EFFECTS PERSIST, OBTAIN MEDICAL TREATMENT.

INGESTION IF SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

SECTION 5: FIRE-FIGHTING MEASURES

FLASH POINT (SETA) 110 F./ 43 C. LOWER EXPLOSIVE LIMIT .7 (%)
UPPER EXPLOSIVE LIMIT 8.9 (%)

FIRE EXTINGUISHING MEDIA
DRY CHEMICAL OR FOAM
WATER FOG.
CARBON DIOXIDE.

UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT OR FIRE.
VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL LONG DISTANCES TO A SOURCE OF IGNITION AND FLASH BACK.
VAPORS CAN FORM EXPLOSIVE MIXTURES IN AIR AT ELEVATED TEMPERATURES.
CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR FIRE.

FB312-91

PAGE 5

SECTION 5: FIRE-FIGHTING MEASURES

MAY DECOMPOSE UNDER FIRE CONDITIONS EMITTING IRRITANT AND/OR TOXIC GASES.

FIRE FIGHTING PROCEDURES

WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS. FIREFIGHTERS SHOULD USE FULL PROTECTIVE CLOTHING, EYE PROTECTION, AND SELF-CONTAINED BREATHING APPARATUS.

HAZARDOUS DECOMPOSITION OR COMBUSTION PRODUCTS

CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN, OXIDES OF SULFUR, TOXIC GASES.

SECTION 6 ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL REGULATIONS.

ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA. SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS. EVACUATE ALL UNNECESSARY PERSONNEL. PLACE COLLECTED MATERIAL IN PROPER CONTAINER. COMPLETE PERSONAL PROTECTIVE EQUIPMENT MUST BE USED DURING CLEANUP.

LARGE SPILLS - SHUT OFF LEAK IF SAFE TO DO SO. DIKE AND CONTAIN SPILL. PUMP TO STORAGE OR SALVAGE VESSELS. USE ABSORBENT TO PICK UP EXCESS RESIDUE. KEEP SALVAGEABLE MATERIAL AND RINSE WATER OUT OF SEWERS AND WATER COURSES. SMALL SPILLS - USE ABSORBENT TO PICK UP RESIDUE AND DISPOSE OF PROPERLY.

SECTION 7 HANDLING AND STORAGE

HANDLING AND STORAGE

STORE BELOW 100F (38C). KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME.

FB312-91

PAGE 6

SECTION 7 HANDLING AND STORAGE

OTHER PRECAUTIONS USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN AND EYES, AND BREATHING OF VAPORS. WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING OR SMOKING. KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE. EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES. GROUND EQUIPMENT WHEN TRANSFERRING TO PREVENT ACCUMULATION OF STATIC CHARGE.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

COMMON NAME : ETHYLBENZENE

CAS NUMBER: 100-41-4

ACGIH(TWA): 100 PPM

ACGIH(STEL): 125 PPM

OSHA(TWA): 100 PPM

COMMON NAME : RHEOLOGICAL ADDITIVE

CAS NUMBER: 121888-66-2

ACGIH(TWA): 10 MG/M3

OSHA(TWA): 10 MG/M3

COMMON NAME : XYLENE

CAS NUMBER: 1330-20-7

ACGIH(TWA): 100 PPM

ACGIH(STEL): 150 PPM

OSHA(TWA): 100 PPM

COMMON NAME : CLAY

CAS NUMBER: 1332-58-7

ACGIH(TWA): 2 MG/M3

OSHA(TWA): 5 MG/M3

COMMON NAME : TITANIUM DIOXIDE

CAS NUMBER: 13463-67-7

ACGIH(TWA): 10 MG/M3

OSHA(TWA): 10 MG/M3

COMMON NAME : ZIRCONIUM CARBOXYLATE

CAS NUMBER: 22464-99-9

ACGIH(TWA): 5 MG/M3

ACGIH(STEL): 10 MG/M3

OSHA(TWA): 5 MG/M3

COMMON NAME : HEAVY SOLVENT NAPHTHA

FB312-91

PAGE 7

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS NUMBER: 64741-65-7
ACGIH(TWA): 100 PPM OSHA(TWA): 500 PPM

COMMON NAME : MEDIUM ALIPHATIC SOLVENT NAPHTHA
CAS NUMBER: 64742-88-7
ACGIH(TWA): 100 PPM OSHA(TWA): 500 X PPM

COMMON NAME : MINERAL SPIRITS
CAS NUMBER: 8054-41-3
ACGIH(TWA): 100 PPM OSHA(TWA): 500 PPM

K AS PETROLEUM DISTILLATES

RESPIRATORY PROTECTION

CONTROL ENVIRONMENTAL CONCENTRATIONS BELOW APPLICABLE EXPOSURE STANDARDS WHEN USING THIS MATERIAL. WHEN RESPIRATORY PROTECTION IS DETERMINED TO BE NECESSARY, USE A NIOSH/MSHA (CANADIAN Z94.4) APPROVED ELASTOMERIC SEALING-SURFACE FACEPIECE RESPIRATOR OUTFITTED WITH ORGANIC VAPOR CARTRIDGES AND PAINT SPRAY (DUST/MIST) PREFILTERS. DETERMINE THE PROPER LEVEL OF PROTECTION BY CONDUCTING APPROPRIATE AIR MONITORING. CONSULT 29CFR1910.134 FOR SELECTION OF RESPIRATORS (CANADIAN Z94.4).

VENTILATION PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS.
USE EXPLOSION-PROOF EQUIPMENT.

PERSONAL PROTECTIVE EQUIPMENT

EYE WASH, SAFETY SHOWER, SAFETY GLASSES OR GOGGLES.
IMPERVIOUS GLOVES, IMPERVIOUS CLOTHING, BOOTS.

FB312-91

PAGE 8

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE:	NOT AVAILABLE	SPECIFIC GRAVITY:	1.107
BOILING RANGE (F/C):	212-417/100-214	WEIGHT PER GALLON:	9.22/ 11.07IMP
%VOLATILE BY VOLUME:	43.21		
PHYSICAL STATE:	LIQUID	APPEARANCE	WHITE
SOLUBILITY IN WATER:	NOT AVAILABLE	PH:	NOT AVAILABLE

SECTION 10: STABILITY AND REACTIVITY

UNDER NORMAL CONDITIONS

STABLE

SEE SECTION 5 FIRE FIGHTING MEASURES

MATERIALS TO AVOID

OXIDIZERS, ACIDS, BASES, AMINES, NITRIC ACID.
STYRENE MONOMER.

CONDITIONS TO AVOID

ELEVATED TEMPERATURES, CONTACT WITH OXIDIZING AGENT, SPARKS,
OPEN FLAME, IGNITION SOURCES.

HAZARDOUS POLYMERIZATION

WILL NOT OCCUR

SECTION 11: TOXICOLOGICAL INFORMATION

COMMON NAME : ETHYLBENZENE

CAS NUMBER: 100-41-4

CARCINOGENICITY LISTED BY:	NTP NO	IARC YES 2B	OSHA NO	ACGIH YES A3
LD50:	3500.00 MG/KG	ORL RAT		
LD50:	2272.00 MG/KG	IPR MOU		
LD50:	17.80 GM/KG	SKN RBT		

COMMON NAME : RHEOLOGICAL ADDITIVE

CAS NUMBER: 121858-66-2

CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
LD50:>	5.00 GM/KG	ORL RAT		

COMMON NAME : XYLENE

FB312-91

PAGE 9

SECTION 11: TOXICOLOGICAL INFORMATION

CAS NUMBER: 1330-20-7

CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
LD50:	>1700.00 MG/KG SKN RBT			
LD50:	4300.00 MG/KG ORL RAT			
LC50:	5000.00 PPM/4HR IHL RAT			

COMMON NAME : CLAY

CAS NUMBER: 1332-58-7

CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
----------------------------	--------	---------	---------	----------

COMMON NAME : TITANIUM DIOXIDE

CAS NUMBER: 13463-67-7

CARCINOGENICITY LISTED BY:	NTP YES 2B	IARC YES 2B	OSHA NO	ACGIH NO
LD50:	24.00 GM/KG ORL RAT			
LC50:	6820.00 MG/M3/4HR IHL RAT			

COMMON NAME : ZIRCONIUM CARBOXYLATE

CAS NUMBER: 22464-99-9

CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
----------------------------	--------	---------	---------	----------

COMMON NAME : ISOPROPYLAMINE DODECYLBENZENESULFONATE

CAS NUMBER: 26264-05-1

CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
----------------------------	--------	---------	---------	----------

COMMON NAME : HEAVY SOLVENT NAPHTHA

CAS NUMBER: 64741-65-7

CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
----------------------------	--------	---------	---------	----------

COMMON NAME : MEDIUM ALIPHATIC SOLVENT NAPHTHA

CAS NUMBER: 64742-88-7

CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
LD50:	28.00 GM/KG SKN RBT			
LD50:	28.00 GM/KG ORL RAT			

COMMON NAME : MINERAL SPIRITS

CAS NUMBER: 8052-41-3

CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
LD50:>	3.00 GM/KG SKN RBT			
LD50:>	5.00 GM/KG ORL RAT			

FB312-91

PAGE 10

SECTION 11: TOXICOLOGICAL INFORMATION

SUPPLEMENTAL HEALTH INFORMATION

CONTAINS A CHEMICAL THAT MAY BE ABSORBED THROUGH SKIN. NOTICE - REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. OTHER EFFECTS OF OVEREXPOSURE MAY INCLUDE TOXICITY TO LIVER, KIDNEY, CENTRAL NERVOUS SYSTEM.

CARCINOGENICITY

STODDARD SOLVENT IIC HAS BEEN SHOWN TO CAUSE KIDNEY TUMORS IN MALE RATS IN A NATIONAL TOXICOLOGY PROGRAM (NTP) STUDY. THESE TUMORS WERE ASSOCIATED WITH A SPECIFIC PROTEIN, ALPHA-2U-MICROGLOBULIN. BECAUSE HUMANS DO NOT PRODUCE THIS PROTEIN STODDARD SOLVENT IIC HAS NOT BEEN CLASSIFIED AS A HUMAN CARCINOGEN.

THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS EVALUATED ETHYLBENZENE AND CLASSIFIED IT AS A POSSIBLE HUMAN CARCINOGEN (GROUP 2B) BASED ON SUFFICIENT EVIDENCE FOR CARCINOGENICITY IN EXPERIMENTAL ANIMALS, BUT INADEQUATE EVIDENCE FOR CANCER IN EXPOSED HUMANS.

IN A 2 YEAR INHALATION STUDY CONDUCTED BY THE NATIONAL TOXICOLOGY PROGRAM (NTP), ETHYLBENZENE VAPOR AT 750 PPM PRODUCED KIDNEY AND TESTICULAR TUMORS IN RATS AND LUNG AND LIVER TUMORS IN MICE. GENETIC TOXICITY STUDIES SHOWED NO GENOTOXIC EFFECTS. THE RELEVANCE OF THESE RESULTS TO HUMANS IS NOT KNOWN.

IN A LIFETIME INHALATION STUDY, EXPOSURE TO 250 MG/M3 TITANIUM DIOXIDE RESULTED IN THE DEVELOPMENT OF LUNG TUMORS IN RATS. THESE TUMORS OCCURRED ONLY AT DUST LEVELS THAT OVERWHELMED THE ANIMALS' LUNG CLEARANCE MECHANISMS AND WERE DIFFERENT FROM COMMON HUMAN LUNG TUMORS IN BOTH TYPE AND LOCATION. THE RELEVANCE OF THESE FINDINGS TO HUMANS IS UNKNOWN BUT QUESTIONABLE.

THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS CLASSIFIED TITANIUM DIOXIDE AS POSSIBLY CARCINOGENIC TO HUMANS (GROUP 2B) BASED ON INADEQUATE EVIDENCE OF CARCINOGENICITY IN HUMANS AND SUFFICIENT EVIDENCE OF CARCINOGENICITY IN EXPERIMENTAL ANIMALS.

FB312-91

PAGE 11

SECTION 11: TOXICOLOGICAL INFORMATION

CONTAINS METHYL ETHYL KETOXIME (MEKO). IN A LIFETIME, INHALATION STUDY, LIVER CARCINOMAS WERE OBSERVED IN RODENTS EXPOSED TO MEKO. THE RELEVANCE TO HUMANS IS UNKNOWN.

REPRODUCTIVE EFFECTS

HIGH EXPOSURES TO XYLENE IN SOME ANIMAL STUDIES, OFTEN AT MATERNALLY TOXIC LEVELS, HAVE AFFECTED EMBRYO/FETAL DEVELOPMENT. THE SIGNIFICANCE OF THIS FINDING TO HUMANS IS NOT KNOWN.

MUTAGENICITY

NO MUTAGENIC EFFECTS ARE ANTICIPATED

TERATOGENICITY

NO TERATOGENIC EFFECTS ARE ANTICIPATED

SECTION 12: ECOLOGICAL INFORMATION

NO ECOLOGICAL TESTING HAS BEEN DONE BY AKZO NOBEL PAINTS LLC ON THIS PRODUCT AS A WHOLE.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

SECTION 14: TRANSPORT INFORMATION

DOT

UN1263, PAINT, COMBUSTIBLE LIQUID, PGIII

IMDG

NOT AVAILABLE

IATA

NOT AVAILABLE

TDG

NOT AVAILABLE

FB312-91

PAGE 12

SECTION 15: REGULATORY INFORMATION

SARA 302	SARA 313	CERCLA 302.4	HAZ AIR POLLUTANT	MARINE POLYTNT
-------------	-------------	-----------------	----------------------	-------------------

CAS NUMBER:	100-41-4	NO	YES	YES	YES	NO
COMMON NAME :	ETHYLBENZENE					
CAS NUMBER:	1330-20-7	NO	YES	YES	YES	NO
COMMON NAME :	XYLENE					

AS OF THE DATE OF THIS MSDS, ALL OF THE COMPONENTS IN THIS PRODUCT ARE LISTED (OR ARE OTHERWISE EXEMPT FROM LISTING) ON THE TSCA INVENTORY.

THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR (CONTROLLED PRODUCTS REGULATIONS) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

SECTION 16: OTHER INFORMATION

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE AT THE TIME OF PREPARATION OF THIS DATA SHEET AND WHICH AKZO NOBEL PAINTS LLC BELIEVES TO BE RELIABLE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA. AKZO NOBEL PAINTS LLC SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS INFORMATION, OR OF ANY PRODUCT, METHOD OR APPARATUS MENTIONED AND YOU MUST MAKE YOUR OWN DETERMINATION OF ITS SUITABILITY AND COMPLETENESS FOR YOUR OWN USE, FOR THE PROTECTION OF THE ENVIRONMENT, AND THE HEALTH AND SAFETY OF YOUR EMPLOYEES AND USERS OF THIS MATERIAL.

COMPLIES WITH OSHA HAZARD COMMUNICATION STANDARD 29CFR1910.1200.